



INTERNATIONAL EQUIPMENT COMPONENTS, INC.

Phone: 562.597.4533 eMail: sales@iec-corp.com

Web: www.iec-corp.com | www.levelingmounts.com

MEDIUM-DUTY LEVELERS

DOUBLE HI-PRO® POLY FIXED STUD

1-1/2" BASE DIAMETER - 2" TALL

DOUBLE HIGH PROFILE POLY BASE FIXED STUD GLIDES


The IEC Double High Profile Steel and Stainless Steel Poly Base Fixed Stud Glide features IEC's Ridge-Grip® design and is ideal for light and medium-duty load requirements. **The high-profile base is useful for raising kitchen equipment, furniture, grocery displays, fitness equipment, electronic equipment and other products for ease of cleaning, sweeping, mopping, ventilation, etc.** The stud will tilt several degrees under load to compensate for unlevel surfaces. Cost-effective for applications not requiring a swivel base. Zinc plated steel stud and black polypropylene base, 1" and 2" thick. Two base sizes to choose from (1-1/2" to 2"). Many sizes available with Top-A-Just® top-end external hex (-HX). You may also request top broached hex, allen drive (-BR).



Top-A-Just® (-HX)



Top-A-Just® (-BR)



Features

- High-profile base
- Ridge-Grip® design
- Loads to 3000 lbs
- Steel and Stainless studs
- Corrosion resistant
- RoHS compliant
- Top hex options

Applications

- Kitchen Equipment
- Displays
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic equipment
- Medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables

Steel	SS	Load	Thread	Hex	A	B	C
Double High Profile Steel and Stainless Steel Poly Base Fixed Stud Glides							
IL140-DHP-4Bx1/2	IL140-DHP-4BSx1/2	100	1/4-20	1/2	1-1/2	1/2	2-5/16
IL140-DHP-4Bx1	IL140-DHP-4BSx1	100	1/4-20	1/2	1-1/2	1	2-5/16
IL140-DHP-4B	IL140-DHP-4BS	100	1/4-20	1/2	1-1/2	1-9/16	2-5/16
IL140-DHP-4Bx2-HX	IL140-DHP-4BSx2-HX	100	1/4-20	1/2	1-1/2	2	2-5/16
IL140-DHP-4Bx2S	IL140-DHP-4BSx2S	100	1/4-20	1/2	1-1/2	2-1/2	2-5/16
IL140-DHP-5Bx3/4	IL140-DHP-5BSx3/4	500	5/16-18	1/2	1-1/2	3/4	2-5/16
IL140-DHP-5Bx15-HX	IL140-DHP-5BSx15-HX	500	5/16-18	1/2	1-1/2	1-1/2	2-5/16
IL140-DHP-5B	IL140-DHP-5BS	500	5/16-18	1/2	1-1/2	1-9/16	2-5/16
IL140-DHP-5Bx25-HX	IL140-DHP-5BSx25-HX	500	5/16-18	1/2	1-1/2	2-1/2	2-5/16
IL140-DHP-5Bx3	IL140-DHP-5BSx3	500	5/16-18	1/2	1-1/2	3	2-5/16
IL140-DHP-5Bx4	IL140-DHP-5BSx4	500	5/16-18	1/2	1-1/2	4	2-5/16
IL140-DHP-6Bx3/4	IL140-DHP-6BSx3/4	1000	3/8-16	1/2	1-1/2	3/4	2-5/16
IL140-DHP-6Bx15-HX	IL140-DHP-6BSx15-HX	1000	3/8-16	1/2	1-1/2	1-1/2	2-5/16
IL140-DHP-6B	IL140-DHP-6BS	1000	3/8-16	1/2	1-1/2	1-9/16	2-5/16
IL140-DHP-6Bx1	IL140-DHP-6BSx1	1000	3/8-16	1/2	1-1/2	1	2-5/16
IL140-DHP-6Bx2	IL140-DHP-6BSx2	1000	3/8-16	1/2	1-1/2	2	2-5/16
IL140-DHP-6Bx2-HX	IL140-DHP-6BSx2-HX	1000	3/8-16	1/2	1-1/2	2	2-5/16
IL140-DHP-6Bx3	IL140-DHP-6BSx3	1000	3/8-16	1/2	1-1/2	3	2-5/16
IL140-DHP-6Bx3-HX	IL140-DHP-6BSx3-HX	1000	3/8-16	1/2	1-1/2	3	2-5/16
IL140-DHP-6Bx4	IL140-DHP-6BSx4	1000	3/8-16	1/2	1-1/2	4	2-5/16
IL140-DHP-6Bx45-HX	IL140-DHP-6BSx45-HX	1000	3/8-16	1/2	1-1/2	4-1/2	2-5/16
IL140-DHP-6Bx6-HX	IL140-DHP-6BSx6-HX	1000	3/8-16	1/2	1-1/2	6	2-5/16
IL140-DHP-6FBx1	IL140-DHP-6FBSx1	1000	3/8-24	1/2	1-1/2	1	2-5/16
IL140-DHP-6FBx2	IL140-DHP-6FBSx2	1000	3/8-24	1/2	1-1/2	2	2-5/16
IL140-DHP-7B	IL140-DHP-7BS	2000	1/2-13	1/2	1-1/2	1-9/16	2-5/16
IL140-DHP-7Bx2	IL140-DHP-7BSx2	2000	1/2-13	1/2	1-1/2	2	2-5/16
IL140-DHP-7Bx2-HX	IL140-DHP-7BSx2-HX	2000	1/2-13	1/2	1-1/2	2	2-5/16
IL140-DHP-7Bx25-HX	IL140-DHP-7BSx25-HX	2000	1/2-13	1/2	1-1/2	2-1/2	2-5/16
IL140-DHP-7Bx3	IL140-DHP-7BSx3	2000	1/2-13	1/2	1-1/2	3	2-5/16
IL140-DHP-7Bx3-HX	IL140-DHP-7BSx3-HX	2000	1/2-13	1/2	1-1/2	3	2-5/16
IL140-DHP-7Bx35-HX	IL140-DHP-7BSx35-HX	2000	1/2-13	1/2	1-1/2	3-1/2	2-5/16
IL140-DHP-7Bx4	IL140-DHP-7BSx4	2000	1/2-13	1/2	1-1/2	4	2-5/16
IL140-DHP-7Bx4-HX	IL140-DHP-7BSx4-HX	2000	1/2-13	1/2	1-1/2	4	2-5/16
IL140-DHP-7Bx5	IL140-DHP-7BSx5	2000	1/2-13	1/2	1-1/2	5	2-5/16
IL140-DHP-7Bx5-HX	IL140-DHP-7BSx5-HX	2000	1/2-13	1/2	1-1/2	5	2-5/16
IL140-DHP-7Bx6-HX	IL140-DHP-7BSx6-HX	1500	1/2-13	1/2	1-1/2	6	2-5/16
IL140-DHP-7Bx8-HX	IL140-DHP-7BSx8-HX	1000	1/2-13	1/2	1-1/2	8	2-5/16
IL140-DHP-7FBx1	IL140-DHP-7FBSx1	2000	1/2-20	1/2	1-1/2	1	2-5/16
IL140-DHP-7FBx2	IL140-DHP-7FBSx2	2000	1/2-20	1/2	1-1/2	2	2-5/16
IL140-DHP-7FBx4	IL140-DHP-7FBSx4	2000	1/2-20	1/2	1-1/2	4	2-5/16
IL140-DHP-8B	IL140-DHP-8BS	2500	5/8-11	5/8	1-1/2	1-9/16	2-5/16
IL140-DHP-8Bx3	IL140-DHP-8BSx3	2500	5/8-11	5/8	1-1/2	3	2-5/16
IL140-DHP-8Bx4	IL140-DHP-8BSx4	2500	5/8-11	5/8	1-1/2	4	2-5/16
IL140-DHP-8Bx5	IL140-DHP-8BSx5	2500	5/8-11	5/8	1-1/2	5	2-5/16
IL140-DHP-9B	IL140-DHP-9BS	3000	3/4-10	3/4	1-1/2	1-9/16	2-5/16
IL140-DHP-9Bx3	IL140-DHP-9BSx3	3000	3/4-10	3/4	1-1/2	3	2-5/16
IL140-DHP-9Bx4	IL140-DHP-9BSx4	3000	3/4-10	3/4	1-1/2	4	2-5/16

**INTERNATIONAL EQUIPMENT COMPONENTS, INC.**

Phone: 562.597.4533 eMail: sales@iec-corp.com

Web: www.iec-corp.com | www.levelingmounts.com

MEDIUM-DUTY LEVELERS**DOUBLE HI-PRO® POLY FIXED STUD****2" BASE DIAMETER - 2" TALL****DOUBLE HIGH PROFILE POLY BASE FIXED STUD GLIDES**

The IEC Double High Profile Steel and Stainless Steel Poly Base Fixed Stud Glide features IEC's Ridge-Grip® design and is ideal for light and medium-duty load requirements. **The high-profile base is useful for raising kitchen equipment, furniture, grocery displays, fitness equipment, electronic equipment and other products for ease of cleaning, sweeping, mopping, ventilation, etc.** The stud will tilt several degrees under load to compensate for unlevel surfaces. Cost-effective for applications not requiring a swivel base. Zinc plated steel stud and black polypropylene base, 1" and 2" thick. Two base sizes to choose from (1-1/2" to 2"). Many sizes available with Top-A-Just® top-end external hex (-HX). You may also request top broached hex, allen drive (-BR).



Top-A-Just® (-HX)




Top-A-Just® (-BR)

Features

- High-profile base
- Ridge-Grip® design
- Loads to 3000 lbs
- Steel and Stainless studs
- Corrosion resistant
- RoHS compliant
- Top hex options

Applications

- Kitchen Equipment
- Displays
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic equipment
- Medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables



Steel	SS	Load	Thread	Hex	A	B	C
Double High Profile Steel and Stainless Steel Poly Base Fixed Stud Glides							
IL141-DHP-4Bx1/2	IL141-DHP-4BSx1/2	100	1/4-20	1/2	2	1/2	2-5/16
IL141-DHP-4Bx1	IL141-DHP-4BSx1	100	1/4-20	1/2	2	1	2-5/16
IL141-DHP-4B	IL141-DHP-4BS	100	1/4-20	1/2	2	1-9/16	2-5/16
IL141-DHP-4Bx2-HX	IL141-DHP-4BSx2-HX	100	1/4-20	1/2	2	2	2-5/16
IL141-DHP-4Bx25	IL141-DHP-4BSx25	100	1/4-20	1/2	2	2-1/2	2-5/16
IL141-DHP-5Bx3/4	IL141-DHP-5BSx3/4	500	5/16-18	1/2	2	3/4	2-5/16
IL141-DHP-5Bx15-HX	IL141-DHP-5BSx15-HX	500	5/16-18	1/2	2	1-1/2	2-5/16
IL141-DHP-5B	IL141-DHP-5BS	500	5/16-18	1/2	2	1-9/16	2-5/16
IL141-DHP-5Bx25-HX	IL141-DHP-5BSx25-HX	500	5/16-18	1/2	2	2-1/2	2-5/16
IL141-DHP-5Bx3	IL141-DHP-5BSx3	500	5/16-18	1/2	2	3	2-5/16
IL141-DHP-5Bx4	IL141-DHP-5BSx4	500	5/16-18	1/2	2	4	2-5/16
IL141-DHP-6Bx3/4	IL141-DHP-6BSx3/4	1000	3/8-16	1/2	2	3/4	2-5/16
IL141-DHP-6Bx15-HX	IL141-DHP-6BSx15-HX	1000	3/8-16	1/2	2	1-1/2	2-5/16
IL141-DHP-6B	IL141-DHP-6BS	1000	3/8-16	1/2	2	1-9/16	2-5/16
IL141-DHP-6Bx1	IL141-DHP-6BSx1	1000	3/8-16	1/2	2	1	2-5/16
IL141-DHP-6Bx2	IL141-DHP-6BSx2	1000	3/8-16	1/2	2	2	2-5/16
IL141-DHP-6Bx2-HX	IL141-DHP-6BSx2-HX	1000	3/8-16	1/2	2	2	2-5/16
IL141-DHP-6Bx3	IL141-DHP-6BSx3	1000	3/8-16	1/2	2	3	2-5/16
IL141-DHP-6Bx3-HX	IL141-DHP-6BSx3-HX	1000	3/8-16	1/2	2	3	2-5/16
IL141-DHP-6Bx4	IL141-DHP-6BSx4	1000	3/8-16	1/2	2	4	2-5/16
IL141-DHP-6Bx45-HX	IL141-DHP-6BSx45-HX	1000	3/8-16	1/2	2	4-1/2	2-5/16
IL141-DHP-6Bx6-HX	IL141-DHP-6BSx6-HX	1000	3/8-16	1/2	2	6	2-5/16
IL141-DHP-6FBx1	IL141-DHP-6FBSx1	1000	3/8-24	1/2	2	1	2-5/16
IL141-DHP-6FBx2	IL141-DHP-6FBSx2	1000	3/8-24	1/2	2	2	2-5/16
IL141-DHP-7B	IL141-DHP-7BS	2000	1/2-13	1/2	2	1-9/16	2-5/16
IL141-DHP-7Bx2	IL141-DHP-7BSx2	2000	1/2-13	1/2	2	2	2-5/16
IL141-DHP-7Bx2-HX	IL141-DHP-7BSx2-HX	2000	1/2-13	1/2	2	2	2-5/16
IL141-DHP-7Bx25-HX	IL141-DHP-7BSx25-HX	2000	1/2-13	1/2	2	2-1/2	2-5/16
IL141-DHP-7Bx3	IL141-DHP-7BSx3	2000	1/2-13	1/2	2	3	2-5/16
IL141-DHP-7Bx3-HX	IL141-DHP-7BSx3-HX	2000	1/2-13	1/2	2	3	2-5/16
IL141-DHP-7Bx35-HX	IL141-DHP-7BSx35-HX	2000	1/2-13	1/2	2	3-1/2	2-5/16
IL141-DHP-7Bx4	IL141-DHP-7BSx4	2000	1/2-13	1/2	2	4	2-5/16
IL141-DHP-7Bx4-HX	IL141-DHP-7BSx4-HX	2000	1/2-13	1/2	2	4	2-5/16
IL141-DHP-7Bx5	IL141-DHP-7BSx5	2000	1/2-13	1/2	2	5	2-5/16
IL141-DHP-7Bx5-HX	IL141-DHP-7BSx5-HX	2000	1/2-13	1/2	2	5	2-5/16
IL141-DHP-7Bx6-HX	IL141-DHP-7BSx6-HX	1500	1/2-13	1/2	2	6	2-5/16
IL141-DHP-7Bx8-HX	IL141-DHP-7BSx8-HX	1000	1/2-13	1/2	2	8	2-5/16
IL141-DHP-7FBx1	IL141-DHP-7FBSx1	2000	1/2-20	1/2	2	1	2-5/16
IL141-DHP-7FBx2	IL141-DHP-7FBSx2	2000	1/2-20	1/2	2	2	2-5/16
IL141-DHP-7FBx4	IL141-DHP-7FBSx4	2000	1/2-20	1/2	2	4	2-5/16
IL141-DHP-8B	IL141-DHP-8BS	2500	5/8-11	5/8	2	1-9/16	2-5/16
IL141-DHP-8Bx3	IL141-DHP-8BSx3	2500	5/8-11	5/8	2	3	2-5/16
IL141-DHP-8Bx4	IL141-DHP-8BSx4	2500	5/8-11	5/8	2	4	2-5/16
IL141-DHP-8Bx5	IL141-DHP-8BSx5	2500	5/8-11	5/8	2	5	2-5/16
IL141-DHP-9B	IL141-DHP-9BS	3000	3/4-10	3/4	2	1-9/16	2-5/16
IL141-DHP-9Bx3	IL141-DHP-9BSx3	3000	3/4-10	3/4	2	3	2-5/16
IL141-DHP-9Bx4	IL141-DHP-9BSx4	3000	3/4-10	3/4	2	4	2-5/16

**INTERNATIONAL EQUIPMENT COMPONENTS, INC.**

Phone: 562.597.4533 eMail: sales@iec-corp.com

Web: www.iec-corp.com | www.levelingmounts.com

MEDIUM-DUTY LEVELERS**HI-PRO® & DOUBLE HI-PRO® POLY FIXED STUD****1-1/2" & 2" BASE DIAMETER****HI-PRO® & DOUBLE HIGH PROFILE METRIC POLY BASE
FIXED STUD GLIDES**

The IEC High Profile & Double High Profile Metric Steel and Stainless Steel Poly Base Fixed Stud Glide feature metric threads and IEC's Ridge-Grip® design and is ideal for light and medium-duty load requirements. **The high-profile base is useful for raising kitchen equipment, furniture, grocery displays, fitness equipment, electronic equipment and other products for ease of cleaning, sweeping, mopping, ventilation, etc.** The stud will tilt several degrees under load to compensate for unlevel surfaces. Cost-effective for applications not requiring a swivel base. Zinc plated steel stud and black polypropylene base, 1" and 2" thick. Two base sizes to choose from (1-1/2" to 2"). Many sizes available with Top-A-Just® top-end external hex (-HX). You may also request top broached hex, allen drive (-BR).



Top-A-Just® (-HX)




Top-A-Just® (-BR)

Features

- High-profile base
- Ridge-Grip® design
- Loads to 3000 lbs
- Steel and Stainless steels
- Corrosion resistant
- RoHS compliant
- Top hex options

Applications

- Kitchen Equipment
- Displays
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic equipment
- Medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables

**METRIC HI-PRO® POLY FIXED STUD LEVELERS**

Steel	SS	Load	Thread	Hex	A	B(mm)	C
High Profile Metric Poly Base Steel and Stainless Steel Fixed Stud Glides							
IL140-M6Bx25	IL140-M6BSx25	100	M6	1/2	1-1/2	25	1-5/16
IL140-M6Bx38	IL140-M6BSx38	100	M6	1/2	1-1/2	38	1-5/16
IL140-M6Bx51	IL140-M6BSx51	100	M6	1/2	1-1/2	51	1-5/16
IL140-M8Bx38	IL140-M8BSx38	500	M8	1/2	1-1/2	38	1-5/16
IL140-M8Bx51	IL140-M8BSx51	500	M8	1/2	1-1/2	51	1-5/16
IL140-M8Bx62	IL140-M8BSx62	500	M8	1/2	1-1/2	62	1-5/16
IL140-M10Bx38	IL140-M10BSx38	1000	M10	1/2	1-1/2	38	1-5/16
IL140-M10Bx51	IL140-M10BSx51	1000	M10	1/2	1-1/2	51	1-5/16
IL140-M10Bx62	IL140-M10BSx62	1000	M10	1/2	1-1/2	62	1-5/16
IL140-M12Bx38	IL140-M12BSx38	2000	M12	1/2	1-1/2	38	1-5/16
IL140-M12Bx51	IL140-M12BSx51	2000	M12	1/2	1-1/2	51	1-5/16
IL140-M12Bx75	IL140-M12BSx75	2000	M12	1/2	1-1/2	75	1-5/16
IL140-M12Bx102	IL140-M12BSx102	2000	M12	1/2	1-1/2	102	1-5/16
IL140-M16Bx51	IL140-M16BSx51	2500	M16	5/8	1-1/2	51	1-5/16
IL140-M16Bx90-BR	IL140-M16BSx90-BR	2500	M16	5/8	1-1/2	90	1-5/16
IL140-M16Bx102	IL140-M16BSx102	2500	M16	5/8	1-1/2	102	1-5/16
IL140-M16Bx115-BR	IL140-M16BSx115-BR	2500	M16	5/8	1-1/2	115	1-5/16

METRIC (Double High Profile) POLY FIXED STUD LEVELERS

Steel	SS	Load	Thread	Hex	A	B(mm)	C
Double High Profile Metric Poly Base Steel and Stainless Steel Fixed Stud Glides							
IL140-DHP-M6Bx25	IL140-DHP-M6BSx25	100	M6	1/2	1-1/2	25	2-5/16
IL140-DHP-M6Bx38	IL140-DHP-M6BSx38	100	M6	1/2	1-1/2	38	2-5/16
IL140-DHP-M6Bx51	IL140-DHP-M6BSx51	100	M6	1/2	1-1/2	51	2-5/16
IL140-DHP-M8Bx38	IL140-DHP-M8BSx38	500	M8	1/2	1-1/2	38	2-5/16
IL140-DHP-M8Bx51	IL140-DHP-M8BSx51	500	M8	1/2	1-1/2	51	2-5/16
IL140-DHP-M8Bx62	IL140-DHP-M8BSx62	500	M8	1/2	1-1/2	62	2-5/16
IL140-DHP-M10Bx38	IL140-DHP-M10BSx38	1000	M10	1/2	1-1/2	38	2-5/16
IL140-DHP-M10Bx51	IL140-DHP-M10BSx51	1000	M10	1/2	1-1/2	51	2-5/16
IL140-DHP-M10Bx62	IL140-DHP-M10BSx62	1000	M10	1/2	1-1/2	62	2-5/16
IL140-DHP-M12Bx38	IL140-DHP-M12BSx38	2000	M12	1/2	1-1/2	38	2-5/16
IL140-DHP-M12Bx51	IL140-DHP-M12BSx51	2000	M12	1/2	1-1/2	51	2-5/16
IL140-DHP-M12Bx75	IL140-DHP-M12BSx75	2000	M12	1/2	1-1/2	75	2-5/16
IL140-DHP-M12Bx102	IL140-DHP-M12BSx102	2000	M12	1/2	1-1/2	102	2-5/16
IL140-DHP-M16Bx51	IL140-DHP-M16BSx51	2500	M16	5/8	1-1/2	51	2-5/16
IL140-DHP-M16Bx90-BR	IL140-DHP-M16BSx90-BR	2500	M16	5/8	1-1/2	90	2-5/16
IL140-DHP-M16Bx102	IL140-DHP-M16BSx102	2500	M16	5/8	1-1/2	102	2-5/16
IL140-DHP-M16Bx115-BRIL	IL140-DHP-M16BSx115-BR	2500	M16	5/8	1-1/2	115	2-5/16

METRIC HI-PRO® POLY FIXED STUD LEVELERS

Steel	SS	Load	Thread	Hex	A	B(mm)	C
High Profile Metric Poly Base Steel and Stainless Steel Fixed Stud Glides							
IL141-M6Bx25	IL141-M6BSx25	100	M6	1/2	2	25	1-5/16
IL141-M6Bx38	IL141-M6BSx38	100	M6	1/2	2	38	1-5/16
IL141-M6Bx51	IL141-M6BSx51	100	M6	1/2	2	51	1-5/16
IL141-M8Bx38	IL141-M8BSx38	500	M8	1/2	2	38	1-5/16
IL141-M8Bx51	IL141-M8BSx51	500	M8	1/2	2	51	1-5/16
IL141-M8Bx62	IL141-M8BSx62	500	M8	1/2	2	62	1-5/16
IL141-M10Bx38	IL141-M10BSx38	1000	M10	1/2	2	38	1-5/16
IL141-M10Bx51	IL141-M10BSx51	1000	M10	1/2	2	51	1-5/16
IL141-M10Bx62	IL141-M10BSx62	1000	M10	1/2	2	62	1-5/16
IL141-M12Bx38	IL141-M12BSx38	2000	M12	1/2	2	38	1-5/16
IL141-M12Bx51	IL141-M12BSx51	2000	M12	1/2	2	51	1-5/16
IL141-M12Bx75	IL141-M12BSx75	2000	M12	1/2	2	75	1-5/16
IL141-M12Bx102	IL141-M12BSx102	2000	M12	1/2	2	102	1-5/16
IL141-M16Bx51	IL141-M16BSx51	2500	M16	5/8	2	51	1-5/16
IL141-M16Bx90-BR	IL141-M16BSx90-BR	2500	M16	5/8	2	90	1-5/16
IL141-M16Bx102	IL141-M16BSx102	2500	M16	5/8	2	102	1-5/16
IL141-M16Bx115-BR	IL141-M16BSx115-BR	2500	M16	5/8	2	115	1-5/16

METRIC (Double High Profile) POLY FIXED STUD LEVELERS

Steel	SS	Load	Thread	Hex	A	B(mm)	C
Double High Profile Metric Poly Base Steel and Stainless Steel Fixed Stud Glides							
IL141-DHP-M6Bx25	IL141-DHP-M6BSx25	100	M6	1/2	2	25	2-5/16
IL141-DHP-M6Bx38	IL141-DHP-M6BSx38	100	M6	1/2	2	38	2-5/16
IL141-DHP-M6Bx51	IL141-DHP-M6BSx51	100	M6	1/2	2	51	2-5/16
IL141-DHP-M8Bx38	IL141-DHP-M8BSx38	500	M8	1/2	2	38	2-5/16
IL141-DHP-M8Bx51	IL141-DHP-M8BSx51	500	M8	1/2	2	51	2-5/16
IL141-DHP-M8Bx62	IL141-DHP-M8BSx62	500	M8	1/2	2	62	2-5/16
IL141-DHP-M10Bx38	IL141-DHP-M10BSx38	1000	M10	1/2	2	38	2-5/16
IL141-DHP-M10Bx51	IL141-DHP-M10BSx51	1000	M10	1/2	2	51	2-5/16
IL141-DHP-M10Bx62	IL141-DHP-M10BSx62	1000	M10	1/2	2	62	2-5/16
IL141-DHP-M12Bx38	IL141-DHP-M12BSx38	2000	M12	1/2	2	38	2-5/16
IL141-DHP-M12Bx51	IL141-DHP-M12BSx51	2000	M12	1/2	2	51	2-5/16
IL141-DHP-M12Bx75	IL141-DHP-M12BSx75	2000	M12	1/2	2	75	2-5/16
IL141-DHP-M12Bx102	IL141-DHP-M12BSx102	2000	M12	1/2	2	102	2-5/16
IL141-DHP-M16Bx51	IL141-DHP-M16BSx51	2500	M16	5/8	2	51	2-5/16
IL141-DHP-M16Bx90-BR	IL141-DHP-M16BSx90-BR	2500	M16	5/8	2	90	2-5/16
IL141-DHP-M16Bx102	IL141-DHP-M16BSx102	2500	M16	5/8	2	102	2-5/16
IL141-DHP-M16Bx115-BR	IL141-DHP-M16BSx115-BR	2500	M16	5/8	2	115	2-5/16